

DERWENT-ACC-NO: 1977-A8757Y

DERWENT-WEEK: 197705

COPYRIGHT 1999 DERWENT INFORMATION LTD

TITLE: Thermally insulating, sound absorbent cladding
for

staeam turbine - with filler between turbine and
cladding
of flowing, incombustible material of high porosity

PATENT-ASSIGNEE: BOWENS S[BOWEI]

PRIORITY-DATA: 1975DD-0189839 (December 3, 1975)

PATENT-FAMILY:

PUB-NO	PUB-DATE	LANGUAGE	PAGES
MAIN-IPC			
DD 123140 A	November 20, 1976	N/A	000
N/A			

INT-CL (IPC): F01D025/08, G10K011/00

ABSTRACTED-PUB-NO: DD 123140A

BASIC-ABSTRACT:

The thermally-insulating, sound-absorbant cladding is used for a gas or steam turbine and has a filler opening at the top and an outlet opening at the bottom, with the space between the turbine and the cladding filled with a flowing non-combustible material of high-porosity.

The cladding may be assembled from sheet metal panels which are prone to vibrate during operation of the turbine, with the filler material, eg sand, preventing the vibrations being transmitted to the cladding. The latter may have a number of openings which can be connected to air lines.

TITLE-TERMS: THERMAL INSULATE SOUND ABSORB CLAD
TURBINE FILL TURBINE CLAD FLOW
INCOMBUSTIBLE MATERIAL HIGH POROUS

DERWENT-CLASS: P86 Q51